

PA-M91



POWER **AUTOMATIX**
ADVANCING FUTURE TECHNOLOGY

MOBILE SURVEILLANCE SOLUTIONS

4G AHD Speed Dome is a video, high-definition wireless video transmission, voice monitoring, intercom, remote control in one of the portable products. It uses high speed processor and embedded operating system, combined with the most advanced H.264 audio and video compression, wireless network transmission, remote control and other technology in the field of IT. The product is simple in appearance, easy to carry, convenient installation, strong function, high reliability and strong anti vibration, waterproof and so on. The equipment can be temporarily installed in the fixed point or moving vehicles. Applicable to the field of mobile application environment, such as: investigation, public security, traffic police, fire, traffic, armed police, courts, forestry, water conservancy, environmental protection, construction, aquatic products, insurance, insurance and other fields.

Product features

- H.264 High profile video compression encoding, dual stream output;
- The remote real-time monitoring, two-way voice intercom;
- The real-time local video stream, multiple resolution and optional
- Local, remote ptz control;
- data storage, can support 2 SD card, each maximum capacity is 128G;
- 3G/4G/WIFI;
- The integrated design, various installation chassis, suitable for different installation, convenient disassembly;
- 360 degree omni-directional tilt, support 200 preset, automatic cruise support;
- Support the battery / external power supply;
- CMS
- Optional:
 - WiFi AP;
 - GPS;

Dimensions

Item	Parameter
Model	M91-DNWW.L
Video	One Video In , One Video Out
Resolution	1280*720
Audio	One Audio In, One Audio Out
Audio Encoder	G.726
Zoom	20X/30X
Night vision	More than 60 meters
PTZ	Pelco-D/P
	Horizontal: 360° Continuous rotation 120°/S
	Vertical : -15°-90°Continuous rotation 60°/S
	Preset point : 200
Storage	Dual SD card storage, each card with the highest support 128G;
Wireless	3G/4G/WIFI
GPS	GPS/BD Optional
Power	Built in battery, can work 6~8 hours, external power supply 19V/3A
Remaining capacity Display	0/25%/50%/75%/100%
Installation method	Suction cup installation, fixed installation chassis (optional), adjustable bracket (optional)
Protection level	IP66
Size (mm)	173*178*281mm (Long * wide * high)
Weight (g)	Bare pager 5kg, Belt protection box 9kg

Accessories

1、 standard Accessories



adapter



power line

2、 Optional Accessories



extension tripod