

PAR-24VAC-16A16

Rack Mount 16A16 Channel CCTV Power Supply



Features

- New with Digital Amp and Volt Meter
- (16A16) 2 x 8 individually fused outputs (PTC)
- Dual modular redundant design
- Fused Short circuit and High Temperature Protection
- External RGB LED status Indicator for easy identification
- Dual External Power On/Off Switch for each of the 8 Channels
- Power Cable with Panel Safety clip for secure AC connection
- Strong metal case
- 2 year warranty
- *AS/NZS61588.1:2008

Specification

MODEL	PAR-24VAC16A16
Number of Channels	2 x 8 Channel
Output Voltage	24VAC + 10%, no load voltage: 26+/- 10%
Total Output Current	2 x 8A - 1A/Channel
Total Output Power	2 x 210VA
PTC Fuse Rating	2.5A@60V
Cooling	Temperature controlled fan assisted cooling
Protection	
General Protection	Each Output has a PTC fuse with External tri-Colour LED indicator.
AC Fuse	T3A Slow Fuse (M205T)
High Temp. Protection	Output shutdown @ 130°C
LED Status Indicator	Green - Channel not in use Blue - Channel In use Red - Channel in short circuit
Operating Temperature	Minus 10 - 40°C maximum
Humidity	20-90% RH
Input Voltage	240VAC @ 50Hz
Thermal Fuse Rating	130°C
Approvals	Ctick, EMC,AS/NZS 61588 .1:2008
Dimension (mm)	440(W) x 279(L) x 67D